



Nanpao solutions support you.

Nan Pao has a strategic investment in R&D throughout all operations. It is this commitment to technological advancement which allows us to develop products, which are at the leading edge of performance in the woodworking industry. We not only lead the technology in PUR hot melts, but we have an extensive range of advanced adhesives for all other applications. For more information on our products, visit the Nan Pao website – www.nanpao.com.

- Your world-wide partner for adhesives !
- 10 manufacturing factories - ISO 9001 certified
- Sold in more than 100 countries !



Contact Information

Nan Pao Resins Chemical Co., Ltd

Head office
Address : No.12, Nanhaipu, Nanhai Vil., Xigang Dist.,
Tainan City 723, Taiwan
Tel : 886-6-7952801-8
Customer service e-mail : info@nanpao.com

Kunshan

Address : No.600, Kunjia Road, Kunshan Economic &
Technological Zone Jiangsu Province, P.R. China
Tel : 86-512-57708888
E-mail : unfactbeijing@gmail.com

Foshan

Tel : 86-769-83364815 ext. 26636
E-mail : platypus612@gmail.com

Dong-Guan

Tel : 86-769-83364815 ext. 26636
E-mail : platypus612@gmail.com

Fuqing

Tel : 0591-8529-1391
E-mail : zzl163@pub5.fz.fj.cn / mjchen@nanpao.com

Vietnam

Address : No.10, Thong Nhat Road, Song Than 2 Industrial
Park, Di An District, Binh Duong Province, Vietnam
Tel : 84-650-3790378
E-mail : tiger_yang@nanpao.com

Thailand

Address : 412 Kor Soi 1c Bangpoo Industrial Tumbon
Preaksa Ampur Muang Samutprakarn 10280, Thailand.
Tel : 662-323-2761~3
E-mail : pari.parichatlai@gmail.com

Indonesia

Address : JL. Pajajaran Raya No. 44, Jatiuwung, Tangerang,
Indonesia
Tel : 021-5918810
E-mail : ying.chuan@nanpao.com

India

Address : 204, Abhishek, off New Link Road, Andheri(W),
Mumbai 400053, India
Tel : 91-22-67418500
E-mail : navin@nanpao.com

Philippines

Address : 6/F Unit 606, Page 1 Bldg. 1215 Acacia St.
Madrigal Business Park, Ayala Alabang Muntinlupa City
1780 Philippines
Tel : 632-8224098
E-mail : rmungcal@nanpao.ph

www.nanpao.com



Woodworking PUR



Woodpow®

YOUR WORLD-WIDE
PARTNER FOR
WOODWORKING INDUSTRY



Leading Teamwork Integrity Efficiency




Founded in 1961, Nan Pao Resins is the number one manufacturer of adhesives, coatings and specialty chemicals in Taiwan. Our production plants are located right throughout Taiwan, China, Southeast Asia and Australia.

We manufacture products with advanced technology and high quality. We provide an excellent service, and as such, we have a very good reputation and supply to major international customers throughout the world.

Woodpow®

Your first choice for:

- World-wide logistics
- First Class glue
- Cost effectiveness
- Best customer services
- Health, safety & environmental protection



Flat Lamination

Product	Viscosity at 120°C (cps)	Characteristics/Applications
Woodpow® PUR-171	10000	1. Medium open time 2. High initial bonding strength 3. For Acrylate, ABS, melamine, PVC/Wood, PVC foam, MDF
Woodpow® PUR-172	30000	1. Short open time 2. High initial bonding strength 3. For PVC panel/PVC foam frame, ABS panel/honey cumb
Woodpow® PUR-175	20000	1. Short open time 2. High initial bonding strength 3. For PVC panel/PVC foam frame, ABS panel/honey cumb
Woodpow® PUR-178	10000	1. Long open time 2. Long PSA tacky time 3. High initial bonding strength 4. For WPC Floor, PVC, ABS, ACRYLIC sheet/Wood, MDF, PVC foam, HPL. Especially for lower surface energy material.
Woodpow® PUR-188	9000	1. Medium open time 2. High initial bonding strength 3. For wood, meatal, PVC, ABS, HPL

Profile Wrapping

Product	Viscosity at 120°C (cps)	Characteristics/Applications
Woodpow® PUR-260	25,000	1. Short open time 2. High initial bonding strength 3. For PVC, paper foil/wood, wood-plastic
Woodpow® PUR-261	15,000	1. Short open time 2. High initial bonding strength 3. For PVC, paper foil/wood, wood-plastic
Woodpow® PUR-263	12,500	1. Short open time 2. High initial bonding strength 3. For PVC, paper foil/wood, Al, wood-plastic
Woodpow® PUR-265	10,000	1. Short open time 2. High initial bonding strength 3. For PVC, paper foil/wood, wood-plastic

Edgebanding

Product	Viscosity at 120°C (cps)	Characteristics/Applications
Woodpow® T-UR066	68,000	1. Appearance: light yellow 2. Good initial bonding strength 3. Good heat & water resistance 4. For ABS, PVC, HPL, wood, phenolic paper, aluminum
Woodpow® T-UR066W	68,000	1. Appearance: white 2. Good initial bonding strength 3. Good heat & water resistance 4. For ABS, PVC, HPL, wood, phenolic paper, aluminum

Cleaner

Product	Characteristics/Applications
T-AA016	1. Special cleaner 2. Easy to use 3. Apply for rollers